



# 18m Diesel/Electric Spider Lift

## MACHINE SPECIFICATION SHEET

### TR18

REACH HEIGHT	17.60m
PLATFORM HEIGHT	15.60m
CLOSED LENGTH	4.78m
CLOSED HEIGHT	1.95m
CLOSED WIDTH	0.89m
HORIZONTAL REACH	8.50m
WIDTH MAX WORKING	3.32m
WIDTH MIN WORKING	3.32m
SAFE WORKING LOAD	200kg
WEIGHT	2,200kg
CAGE DIMENSIONS	1.70x1.42m
GRADEABILITY	35.5% (19.7°)
CAGE ROTATION	180°
IPAF CATEGORY	1b
SLEW	355°
UP AND OVER CLEARANCE	8.20m
MINIMUM SETUP AREA	3.32x 5.12m (WxL)
TRACK SURFACE AREA	1.45x0.20m
DRIVE SPEED	1.5kph
MAXIMUM SETUP INCLINE	12°/21.0%
NO. OUTRIGGER POSITIONS	1 fixed
POWER	DIESEL/ELECTRIC
FEATURED MODEL	EASY LIFT R180



With a working height of 17.60m, a maximum horizontal outreach of 8.5m and a basket load of 200kg, the R180 is the ideal device for a variety of uses. With a total weight of 2,200kg, a minimum passage width of 0.89m and a height of 1.95m, this track mounted work platform is suitable for narrow access routes in the field and for areas of application with low floor loads. The device with fully hydraulic control has a width-adjustable chain chassis and is very maneuverable with a length of 4.78m. The work basket can be rotated 180° and removed, reducing the minimum length to only 4.78m. The outrigger-area is 3.10 x 3.10m.

The information provided is for guidance only. It may change at any time in accordance with manufacturer's specification. Variable jacking will envelope. Outreach is variable depending on load, angle of rotation and outrigger configuration.

